

Hardware overview

# Signature Pads

*Specifications  
at a glance*



WACOM® for Business

























## Sign Pad Overview




### General Specifications

## STU-540

## STU-430

	<b>Dimensions (W x H x D)</b>	6.4 x 6.2 x 0.4 inches / 163 x 157 x 10 mm	6.3 x 6.9 x 0.4 inches / 161 x 174 x 11 mm
	<b>Weight (including stand)</b>	0.6 lbs / 275 g	0.6 lbs / 280 g
	<b>Main body color</b>	Black	Gray
	<b>Power supply</b>	USB bus powered	Via USB, no additional power adapter required
	<b>Power consumption</b>	2.5 W maximum	1.0 W maximum
	<b>Communication interface</b>	USB/VCP/RS-232	USB
<b>LCD Display</b>			
	<b>Display Type</b>	Amorphous TFT LCD	F-STN Positive Reflective
	<b>Cover plate surface</b>	AG etched glass	Tempered glass
	<b>Native resolution</b>	800 x 480 pixels	320 x 200 pixels
<b>Pad and pen</b>			
	<b>Reading Technology</b>	Electromagnetic Resonance (EMR)	Electromagnetic Resonance (EMR)
	<b>Active area size</b>	4.3 x 2.6 inches / 108 x 65 mm	3.8 x 2.4 inches / 96 x 60 mm
	<b>Coordinate resolution</b>	2540 lpi / 0.01 mm/pt (non-interpolated)	2540 lpi / 0.01 mm/pt (non-interpolated)
	<b>Coordinate accuracy</b>	±0.02 inches / ±0.5 mm (center)	±0.02 inches / ±0.5 mm (center)
	<b>Report rate</b>	200 points per second (non-interpolated)	200 points per second (non-interpolated)
	<b>Pressure levels</b>	1024 (non-interpolated)	1024 (non-interpolated)
	<b>Encryption</b>	AES256 / RSA2048	AES256 / RSA2048
<b>Miscellaneous</b>			
	<b>Pen storage</b>	Pen compartment	Pen tray
	<b>Connectivity security</b>	USB cable locking system	USB cable locking system
	<b>Data security</b>	Real time image capture without data storage. Internal memory for images only.	Real time signature capture without internal pad memory
	<b>Security lock slot</b>	Yes, Kensington	Yes, Kensington
	<b>Operating temperature, relative humidity</b>	+41° F to +104° F / +5° C to +40° C, (humidity 30 % to 80 % RH, no condensing)	+41° F to +104° F / +5° C to +40° C, (humidity 30 % to 80 % RH, no condensing)
	<b>Storage temperature, relative humidity</b>	-4° F to +140° F / -20° C to +60° C, (humidity 30% to 90% RH, no condensing)	-4° F to +140° F / -20° C to +60° C, (humidity 30% to 90% RH, no condensing)
	<b>Signature software compatibility</b>	Compatible with Windows signature / eSign software and Wacom's sign pro PDF and sign pro PDF Plug-in for Adobe Acrobat. For Windows, C++, .Net and Java development libraries available for developers (contact us for library and software availability in other development languages and platforms)	Compatible with Windows signature / eSign software and Wacom's sign pro PDF and sign pro PDF Plug-in for Adobe Acrobat. For Windows, C++, .Net and Java development libraries available for developers (contact us for library and software availability in other development languages and platforms)
	<b>Package content</b>	Signature pad, cordless and battery-free pen, USB cable (9.84 ft / 3 m), quick start guide, pen tether (nylon fiber, 19.7 inch / 50 cm)	Signature pad, cordless and battery-free pen, USB cable (9.84 ft / 3 m), quick start guide, pen tether (nylon fiber, 19.7 inch / 50 cm)

# More human



# More digital



## Japan (HQ)

For more information please contact:  
Wacom Co., Ltd. · Sumitomo Fudosan Shinjuku Grand Tower 31F, 35F,  
8-17-1 Nishi-Shinjuku, Shinjuku-ku, Tokyo 160-6131, Japan  
vm-info@wacom.co.jp · 03-5337-6706



## Americas

For more information please contact / Pour de plus amples informations,  
veuillez contactez / Para obtener información adicional, póngase en contacto  
con: Wacom Technology Corporation · 12121 NE 99th Street, Suite 2140,  
Vancouver, WA 98682 USA  
esign@wacom.com · 1-503-525-3100



## Europe, Middle East and Africa

For more information please contact / Pour de plus amples informations,  
veuillez contactez / Para obtener información adicional, póngase en contacto  
con: Wacom Europe GmbH · Zollhof 11-15, 40221 Düsseldorf, Germany  
solutions@wacom.eu · +49 211 385 48 0



## China (Mainland)

For more information please contact:  
Wacom China Corporation · 518, West Wing Office, China World Trade Center,  
No. 1 Jianguomenwai Avenue, Chaoyang District, Beijing 100004, China  
WW@wacom.com · 400-810-5460

## Hong Kong

For more information please contact:  
Wacom Hong Kong Ltd. · Office 107G, 17/F, Tower I, Grand Century Place,  
193 Prince Edward Road West, Mong Kok, Hong Kong, China  
e-signature@wacom.com · +852 2573 9322



## Australia

For more information please contact:  
Wacom Australia Pty. Ltd. · Ground floor, Building 1, 3 Richardson Place,  
North Ryde, NSW, 2113, Australia  
Contactapbs@Wacom.com · +61 2 9422 6730

## Korea

For more information please contact:  
Wacom Korea Co., Ltd. · Rm #1211, 12F, KGIT Sangam Center, 402 Worldcup  
Bukro, Mapo-gu, Seoul 03925, Korea  
Contactapbs@Wacom.com · 080-800-1231

## Singapore

For more information please contact:  
Wacom Singapore Pte. Ltd. · 5 Temasek Boulevard, #12-09, Suntec Tower Five,  
Singapore 038985, Contactapbs@Wacom.com · (503) 525-3100

## India

For more information please contact:  
Wacom India Pvt. Ltd. · 426, Tower B, DLF Building Jasola District Centre,  
Mathura Road, New Delhi 110025 India, Contactapbs@Wacom.com  
Customer Support: 000-800-100-4159, +91-11-47239412

[wacom.com/for-business](https://wacom.com/for-business)

© 2025 Wacom Co., Ltd.