Data Sheet

STU-540 5-inch color Signature Pad



Wacom® for Business

STU-540

The premium eSignature solution



Product Overview

The STU-540 signature pad is Wacom's most advanced and robust premium electronic signature device. It is ideal for high-traffic environments where in-person handwritten electronic signatures are required to confirm transactions, such as at bank teller desks, hotel check-ins, shop purchases or clinic registrations. The 5-inch high-resolution color LCD screen with hardened glass provides an attractive point of sale signing area with a paper-like feel and superb durability. When not in signature mode, it can also be used for displaying advertising, promotions or branding. A broad range of connectivity options ensure maximum deployment flexibility, including multiple alternatives for virtualized desktop environments. Transaction security is supported with advanced encryption built-in.

Key Features & Benefits

- Low maintenance costs thanks to high durability and the patented cordless, batteryfree digital pen
- Biometrically accurate signatures
 using the digital pen with 1024 levels
 of pressure sensitivity
- High durability and a natural, paper-like feel enabled by the hardened glass with anti-glare screen treatment
- Secure transactions enabled by stateof-the-art AES256 / RSA2048 encryption
- Support for virtualized environments through the Virtual COM Port (VCP) for compatibility with Citrix XenDesktop and XenApp v6.5 and later
- Customizable key pad and PIN pad enabling input using graphic images or numerals

- Attractive signature rendering through the use of WILL™ (Wacom Ink Layer Language) technology that renders the best and most authentic-looking representation of handwritten electronic signatures
- Enhanced signature traceability through a UID (Unique hardware ID) for identifying the exact signature pad unit used for a particular signature and other inputs
- Straightforward integration of signature pad support into applications through the WILL™ SDK (Software Development Kit) for Signature
- Ability to display promotional material through an upgraded USB protocol and internal image storage that enables ads to be shown at natural speeds with no delays

Wacom° for Business

General Specifications

	Dimensions (W x H x D)	6.4 x 6.2 x 0.4inches / 163 x 157 x 10 mm
	Weight (including stand)	0.6 lbs / 275 g
(°°)	Main body color	Black
7	Power supply	USB bus powered
\$	Power consumption	2.5 W maximum
\rightleftharpoons	Communication interface	USB/VCP/RS-232
	LCD Display	
	Display Type	TFT
	Cover plate surface	AG etched glass
***	Native resolution	800 x 480 pixels
	Pad and Pen	
<u>_</u>	Reading Technology	Electromagnetic Resonance (EMR)
	Active area size	4.3 x 2.6 inches / 108 x 65 mm
X	Coordinate resolution	2540 lpi / 0.01 mm/pt (non-interpolated)
•	Coordinate accuracy	±0.02 inches / ±0.5 mm (center)
	Report rate	200 points per second (non-interpolated)
	Pressure levels	1024 (non-interpolated)

W∂COM® for Business

Miscellaneous

	Pen storage	Pen compartment
$\overrightarrow{\mathbb{G}} \overset{\longleftarrow}{\longleftrightarrow}$	Connectivity security	USB cable locking system
	Data security	Real time image capture without data storage. Internal memory for images only.
\bigcirc	Security lock slot	Yes, Kensington
₽	Operating temperature, relative humidity	+41° F to +104° F (+5° C to +40° C), (humidity 30 % to 80 % RH, no condensing)
	Storage temperature, relative humidity	-4° F to +140° F (-20° C to +60° C), (humidity 30% to 90% RH, no condensing)
	Signature software compatibility	Compatible with Windows signature / eSign software and Wacom's sign pro PDF and sign pro PDF Plug-in for Adobe Acrobat. For Windows, C++, .Net and Java development libraries available for developers (contact us for library and software availability in other development languages and platforms)
	Package content	Signature pad, cordless and battery-free pen, USB cable (9.84 ft / 3 m), quick start guide, pen tether (nylon fiber, 19.7 inch / 50 cm)

More human





Japan (HQ)

For more information please contact:

Wacom Co., Ltd. · Sumitomo Fudosan Shinjuku Grand Tower 31F, 35F, 8-17-1 Nishi-Shinjuku, Shinjuku-ku, Tokyo 160-6131, Japan vm-info@wacom.co.jp · 03-5337-6706



Americas

For more information please contact / Pour de plus amples informations, veuillez contacte / Para obtener información adicional, póngase en contacto con: Wacom Technology Corporation · 12121 NE 99th Street, Suite 2140, Vancouver, WA 98682 USA esign@wacom.com · 1-503-525-3100



Europe, Middle East and Africa

For more information please contact / Pour de plus amples informations, veuillez contacte / Para obtener información adicional, póngase en contacto con: Wacom Europe GmbH · Zollhof 11-15, 40221 Düsseldorf, Germany solutions@wacom.eu · +49 211 385 48 0



China (Mainland)

For more information please contact:

Wacom China Corporation · 518, West Wing Office, China World Trade Center,

No. 1 Jianguomenwai Avenue, Chaoyang District, Beijing 100004, China

WW@wacom.com · 400-810-5460

Hong Kong

For more information please contact:

Wacom Hong Kong Ltd. · Office 107G, 17/F, Tower I, Grand Century Place,
193 Prince Edward Road West, Mong Kok, Hong Kong, China
e-signature@wacom.com · +852 2573 9322



Australia

For more information please contact:

Wacom Australia Pty. Ltd. · Ground floor, Building 1, 3 Richardson Place,
North Ryde, NSW, 2113, Australia

Contactapbs@Wacom.com · +61 2 9422 6730

Korea

For more information please contact:

Wacom Korea Co., Ltd. · Rm #1211, 12F, KGIT Sangam Center, 402 Worldcup
Bukro, Mapo-gu, Seoul 03925, Korea

Contactapbs@Wacom.com · 080-800-1231

Singapore

For more information please contact: Wacom Singapore Pte. Ltd. \cdot 5 Temasek Boulevard, #12-09, Suntec Tower Five, Singapore 038985, Contactapbs@Wacom.com \cdot (503) 525-3100

India

For more information please contact:

Wacom India Pvt. Ltd. · 426, Tower B, DLF Building Jasola District Centre,

Mathura Road, New Delhi 110025 India, Contactapbs@Wacom.com

Customer Support: 000-800-100-4159, +91-11-47239412

wacom.com/for-business

© 2025 Wacom Co., Ltd.